



INCORPORATED IN VICTORIA

1 / 2 DALKEITH DRIVE, DROMANA VICTORIA, AUSTRALIA, 3936.

FACTORY AND OFFICE :- TELEPHONE : 03 5981 4791.

FAX : 03 5981 4792.

MATERIAL SAFETY DATA SHEET

Date of Issue 1/01/2013

Company Name & Address

Scour Pads (Aust) Pty Ltd
1 / 2 Dalkeith Drive
Dromana Vic. 3936

Telephone

Office:- 03 5981 4791
Fax :- 03 5981 4792

Worksafe Hazard Assessment: Not classified as hazardous according to the criteria of Worksafe Australia.

IDENTIFICATION

PRODUCT NAME :

Eze-lap Lapping Compound Oil Based Fluid

Oil Based Fluids are identified by the letters "OF" which appear after the grade.

Grades: - 2A700 OF H500 OF H240 OF
H700 OF H320 OF H150 OF

Standard Pack size: - 500 GMS.

H120 OF

UN No. - None allocated

Hazchem Code - Not assigned

CAS No. Not relevant

Other Names - This MSDS is meant for the above listed range of Products, all of which are "OF" Oil Based Fluids.

Dangerous Goods Class - None allocated

Sub Risk Class - Not assigned

Packaging Group - None allocated

EPG: None allocated

Poison Schedule - Not scheduled.

Product Type - Oil based Abrasive compound..

Chemical Family - Mixture of paraffinic base oils and Abrasive grains.

Uses - Used in small quantities for Lapping valve seats.

Physical appearance & Properties:

Appearance & Odour - Cream to Brown coloured material of Cream like consistency - liquid form with Mineral oil odour.

Chemical Reactivity - Stable. Reacts with strong oxidizing agents.

Solubility in Water - Negligible.

Corrosiveness - Not corrosive.

<u>Property</u>	<u>Value</u>	<u>UOM</u>	<u>Temp.</u>
Viscosity	19cst		40 Degrees C
Melting Point	Not available	Deg C	
Vapour Pressure	Not available	less than 0.001 @ 20 Degrees C.	
IBP	Not available	Deg C	
FBP	Not available	Deg C	
Evaporation Rate	Not available	-	
Vap Dens (Air=1)	>1	-	
Fire Explosion Hazard			
Flash Point	Typically 248	Deg C	
Autoignition	Not available	Deg C	
% Volatiles	Not available	-	
LEL	Not available	%v/v	
UEL	Not available	%v/v	

INGREDIENTS

Refined Mineral Oil (complex blend of Parrafinic, Naphenic and Aromatic Hydrocarbons). Proportion high 60% - 90%
Aluminium Oxide - Proportion 10% - 40%

This is a commercial product and the exact ratio of components may vary. Trace quantities of impurities are also likely.

HEALTH HAZARD

- Eye - The Abrasive Grains present in this product would be irritative to the eye causing redness and a tearing sensation.
- Swallowed - Slightly toxic may cause gastric irritation.
- Skin - Mildly irritating to the skin. Prolonged or repeated skin contact may cause dermatitis due to defatting effect.

FIRST AID

If swallowed do not induce vomiting, seek medical advice.

Eye - If this product comes in contact with the eye, hold open and wash with running water, ensure irrigation under eyelids by occasionally lifting them. Do not try to remove contact lenses unless trained. If irritation is evident seek medical advise.

Skin - If this product comes in contact with the skin, wash thoroughly with soap and water. Remove contaminated clothing and footwear. Ensure contaminated clothing is washed before using again.

PRECAUTIONS FOR USE

Exposure Standards

Worksafe Exposure standard :- time weighted average (TWA) 5 mg/m³ (oil mist)
short term exposure limit (STEL) 10 mg/m³ (oil mist).

Engineering Controls

Special ventilation is not normally required due to the low volatility of the product at normal temperatures. However, in the operation of certain equipment or at elevated temperatures, mists or vapour may be generated and exhaust ventilation should be provided to maintain airborne concentration levels below the exposure standard.

Personal Protection

The use of eye protection is suggested when using this product.

Avoid contact with the skin and eyes and avoid breathing vapours or mists. When exposure is likely, personal protective equipment in a combination appropriate to the degree and nature of exposure, should be selected from the following list :-

- (1) Eye protection. Consult AS 1335 & AS/NZS 1337 for information concerning eye protection.
- (2) PVC Gloves
- (3) PVC apron and sleeves, or full PVC covering
- (4) PVC or rubber boots

Where the concentration of vapour or mist is expected to approach the exposure limit, the following additional equipment is recommended :-

RESPIRATORY PROTECTION

A face mask or respirator may be used when the product is being used in dusty or confined areas. Otherwise it is usually safe to not use respiratory protection. However, there may be other circumstances where use of a mask or other device is preferred. Use judgement. For help in selecting suitable equipment consult AS/NZS 1715.

CONTAMINATION

If contamination occurs, change clothing and discard internally contaminated gloves and footwear. Launder contaminated clothing before use.

Observe good personal hygiene.

Eye wash fountains and safety showers should be available for emergency use.

REFERENCES

For detailed advice on Personal Protective equipment, refer to the following Australian Standards :-

HB 9 (Handbook 9)	Manual of industrial personal protection.
AS 1337	Eye protectors for industrial applications.
AS 1715	Selection, use and maintenance of respiratory, protective devices.
AS 1716	Respiratory protective devices.

FLAMMABILITY

Combustible liquid. Will not burn unless preheated.

Refer to AS 1940 - Storage and handling of flammable and combustible liquids and AS 2865 - Safe working in a confined space, for more specific information on these subjects.

SAFE HANDLING INFORMATION

Storage and Transport

Classified as a class C2 combustible liquid for storage and handling purposes. Store in a well ventilated place away from ignition sources, oxidizing agents foodstuffs and clothing. Keep containers closed when not in use.

Spills and Disposal

Extinguish or remove all sources of ignition. Contain the spill with sand or earth and take up with a vacuum or absorb with absorbent material, sand or earth. Place used absorbent in suitable sealed containers and follow state or local authority regulations and guidelines for disposal of the waste. Clean area with detergent and water. Do not allow product to enter drains, sewers or water courses - inform the local authorities if this occurs.

Fire/Explosion Hazard

There is no explosion hazard from this material under normal circumstances. Combustible. Combustion products include oxides of carbon. Use foam, CO2 or dry powder to extinguish fire.

OTHER INFORMATION

Long term animal experiments have shown that any health risks are associated with the level of aromatic and polycyclic constituents contained within the Mineral Oil used within these products. These constituents are removed during the manufacturing process to a level at which no health risks are expected as a result of normal handling.
